

92

overhangs the opening.

60. (Amended) A method of making an antifuse in an integrated-circuit assembly, the method comprising:

[a step for] forming an opening in an insulative layer, with the opening exposing at least one conductor;

[a step for] forming a metal layer in the opening;

[a step for] forming a metal-oxide layer on the metal layer and within the opening,

[a step for] forming a conductive layer on the metal-oxide layer and within the opening;

[a step for] forming at least one conductive member on the insulative layer which overhangs the opening; and

[a step for] at least partially saturating the metal layer with a gas comprising more than trace quantities of hydrogen or nitrogen.

卷之三

Remarks

The specification has been amended to add priority information.

Claims 52 and 60 have been amended, and claims 72-94 have been added. Claims 1-94 are pending in this application.

Respectfully submitted,

LEONARD FORBES ET AL.

By their Representatives.

SCHWEGMAN, LUNDBERG, WOESSNER & KLUTH, P.A.
P.O. Box 2938
Minneapolis, MN 55402
(612) 349-9593

Date 30 Aug-19 2001

By

Eduardo E. Drake
Reg. No. 40,594

"Express Mail" mailing label number: EL 671640564 US
Date of Deposit: August 30, 2001

Date of Deposit: August 30, 2001
This paper or fee is being deposited on the date indicated above with the United States Postal Service pursuant to 37 CFR 1.10, and is addressed to the Commissioner for Patents, Box Patent Application, Washington, D.C. 20231.